## §80.8

- (i) Business or corporate name and address of the distributor.
  - (ii) Quantity of gasoline received.
  - (iii) Date of receipt.
- (b) Upon request by the Administrator, the Regional Administrator, or their delegates, any retailer shall provide documentation of his annual total sales volume in gallons of gasoline for each retail outlet for each calendar year beginning with 1971.
- (c) Any refiner, distributor, wholesale purchaser-consumer, retailer, or importer shall provide such other information as the Administrator or his authorized representative may reasonably require to enable him to determine whether such refiner, distributor, wholesale purchaser-consumer, retailer, or importer has acted or is acting in compliance with sections 211(c) and 211(n) of the Act and the regulations thereunder and shall, upon request of the Administrator or his authorized representative, produce and allow reproduction of any relevant records at all reasonable times. Such information may include but is not limited to records of unleaded gasoline inventory at a wholesale purchaserconsumer facility or a retail outlet, unleaded pump meter readings at a wholesale purchaser-consumer facility or a retail outlet, and receipts providing the date of acquisition of signs, labels, and nozzles required by §80.22. No person shall be required to furnish information requested under this paragraph if he can establish that such information is not maintained in the normal course of his business.

(Secs. 211, 301, Clean Air Act, as amended (42 U.S.C. 1857f-6c, 1857g))

 $[40~\mathrm{FR}~36336,~\mathrm{Aug}.~20,~1975,~\mathrm{as}$  amended at 42 FR 45307, Sept. 9, 1977; 47 FR 49332, Oct. 29, 1982; 61 FR 3837, Feb. 2, 1996]

## §80.8 Sampling methods for gasoline and diesel fuel.

The sampling methods specified in this section shall be used to collect samples of gasoline and diesel fuel for purposes of determining compliance with the requirements of this part.

(a) Manual sampling. Manual sampling of tanks and pipelines shall be performed according to the applicable procedures specified in American Society for Testing and Materials (ASTM)

method D 4057-95(2000), entitled "Standard Practice for Manual Sampling of Petroleum and Petroleum Products."

- (b) Automatic sampling. Automatic sampling of petroleum products in pipelines shall be performed according to the applicable procedures specified in ASTM method D 4177–95(2000), entitled "Standard Practice for Automatic Sampling of Petroleum and Petroleum Products."
- (c) Sampling and sample handling for volatility measurement. Samples to be analyzed for Reid Vapor Pressure (RVP) shall be collected and handled according to the applicable procedures in ASTM method D 5842–95(2000), entitled "Standard Practice for Sampling and Handling of Fuels for Volatility Measurement."
- (d) Sample compositing. Composite samples shall be prepared using the applicable procedures in ASTM method D 5854-96(2000), entitled "Standard Practice for Mixing and Handling of Liquid Samples of Petroleum and Petroleum Products."
- (e) Incorporations by reference. ASTM standard practices D 4057-95(2000), D 4177-95(2000), D 5842-95(2000), and D 5854-96(2000), are incorporated by reference. These incorporations by reference were approved by the Director of the Federal Register in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Copies may be obtained from the American Society for Testing and Materials, 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959. Copies may be inspected at the Air Docket Section (LE-131), room M-1500, U.S. Environmental Protection Agency, Docket No. A-97-03, 401 M Street, SW., Washington, DC 20460, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go http://www.archives.gov/ to:

 $\begin{array}{cccc} federal\_register/\\ code\_of\_federal\_regulations/\\ ibr\_locations.html. \end{array}$ 

[67 FR 8736, Feb. 26, 2002]

## §80.9 Rounding a test result for determining conformance with a fuels standard.

(a) For purposes of determining compliance with the fuel standards of 40